

Package: mountainplot (via r-universe)

October 10, 2026

Title Mountain Plots, Folded Empirical Cumulative Distribution Plots

Version 1.4

Description Lattice functions for drawing folded empirical cumulative distribution plots, or mountain plots. A mountain plot is similar to an empirical CDF plot, except that the curve increases from 0 to 0.5, then decreases from 0.5 to 1 using an inverted scale at the right side. See Monti (1995)
<doi:10.1080/00031305.1995.10476179>.

License MIT + file LICENSE

URL <https://kwstat.github.io/mountainplot/>,
<http://kwstat.github.io/mountainplot/>

BugReports <https://github.com/kwstat/mountainplot/issues>

Imports lattice, stats

Suggests knitr, latticeExtra, rmarkdown, testthat

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.3.3

Repository <https://kwstat.r-universe.dev>

Date/Publication 2025-10-04 00:49:54 UTC

RemoteUrl <https://github.com/kwstat/mountainplot>

RemoteRef HEAD

RemoteSha 79ec6cdb51bae6cbd8a841e4a7575a7b73bb8caf

Contents

mountainplot	2
panel.mountainplot	3
prepanel.mountainplot	4
Index	5

mountainplot

Mountainplot

Description

A mountain plot is similar to an empirical CDF, but `_decreases_` from .5 down to 1, using a separate scale on the right axis.

Usage

```
mountainplot(x, data, ...)

mountainplotyscale.components(...)

## S3 method for class 'formula'
mountainplot(
  x,
  data = NULL,
  prepanel = "prepanel.mountainplot",
  panel = "panel.mountainplot",
  ylab = gettext("Folded Empirical CDF"),
  yscale.components = mountainplotyscale.components,
  scales = list(y = list(alternating = 3)),
  ...
)

## S3 method for class 'numeric'
mountainplot(x, data = NULL, xlab = deparse(substitute(x)), ...)
```

Arguments

<code>x</code>	Variable in the data.frame 'data'.
<code>data</code>	A data frame
<code>...</code>	Other arguments
<code>prepanel</code>	The prepanel function. Default "prepanel.mountainplot".
<code>panel</code>	The panel function. Default "panel.mountainplot".
<code>ylab</code>	Vertical axis label.
<code>yscale.components</code>	Function for drawing left and right side axes.
<code>scales</code>	The "scales" argument used by lattice functions.
<code>xlab</code>	Horizontal axis label.

Details

Note that `'mountainplotyscale.components'` is not intended to be called by the user, but is used by lattice to configure the right-axis ticks and labels.

Value

A lattice object

References

K. L. Monti. (1995). Folded empirical distribution function curves-mountain plots. *The American Statistician*, 49, 342-345. <http://www.jstor.org/stable/2684570>

Xue, J. H., & Titterington, D. M. (2011). The p-folded cumulative distribution function and the mean absolute deviation from the p-quantile. *Statistics & Probability Letters*, 81, 1179-1182. <https://doi.org/10.1016/j.spl.2011.03.014>

Examples

```
data(singer, package = "lattice")
singer <- within(singer, {
  section <- voice.part
  section <- gsub(" 1", "", section)
  section <- gsub(" 2", "", section)
  section <- factor(section)
})
mountainplot(~height, data = singer, type='b')
mountainplot(~height|voice.part, data = singer, type='p')
mountainplot(~height|section, data = singer, groups=voice.part, type='l',
  auto.key=list(columns=4), as.table=TRUE)
```

panel.mountainplot	<i>The panel function for mountainplot</i>
--------------------	--

Description

The panel function for mountainplot

Usage

```
panel.mountainplot(x, type = "s", groups = NULL, ref = TRUE, ...)
```

Arguments

x	The data to be plotted.
type	The type of ecdf line to use. Default is 's' square.
groups	Variable to use for grouping
ref	If TRUE, draw horizontal reference lines at 0,1
...	Other arguments

prepanel.mountainplot *The prepanel function for mountainplot*

Description

The prepanel function for mountainplot

Usage

```
prepanel.mountainplot(x, ...)
```

Arguments

x	The data to be plotted.
...	Other arguments

Index

`mountainplot`, [2](#)
`mountainplotyscale.components`
 `(mountainplot)`, [2](#)

`panel.mountainplot`, [3](#)
`prepanel.mountainplot`, [4](#)